## RSYC / RMSIR SAFETY CHECK LIST



Based on

## WORLD SAILING OFFSHORE SPECIAL REGULATIONS

Category 4 for Multihulls with modification.

BOAT NAME	
RMSIR ENTRY REF SAIL NO	
PERSON IN CHARGE PHONE	
SKIPPER PHONE	
Maximum number of crew on board during this regatta including skipper:	
IMPORTANT: An inspection is carried out only as a guide. An inspecto reduce the complete and unlimited responsibility of the owner and the pe	
1.02 Responsibility of Person in Charge	
1.02.1 The safety of a yacht and her crew is the sole and inescapable responsi in charge who must do his best to ensure that the yacht is fully found, thorough manned by an experienced crew who have undergone appropriate training an to face bad weather. He must be satisfied as to the soundness of hull, spars, riggear. He must ensure that all safety equipment is properly maintained and stocrew know where it is kept and how it is to be used. He shall also nominate a puthe responsibilities of the Person in Charge in the event of his incapacitation.	hly seaworthy and d are physically fit gging, sails and all owed and that the
1.02.2 Neither the establishment of these Special Regulations, their use by ra the inspection of a yacht under these Special Regulations in any way limi complete and unlimited responsibility of the person in charge.	
<ul><li>1.02.3 Decision to race -The responsibility for a yacht's decision to participate i continue racing is hers alone</li><li>RRS Fundamental Rule 4.</li></ul>	n a race or to
"I hereby declare that I am the owner, skipper or person in charge and that understood and agree to comply with World Sailing Offshore Special Reparticular 1.02.1, 1.02.2, and 1.02.3 (Responsibility of Person in Charge)". that the information that I have given in the safety checklist form is true a	egulations and in . I further declare
(Signature)	

Safety Checklist continued overleaf – this must be completed for all boats.

This form can be scanned and sent to <a href="mailto:safety@rmsir.com">safety@rmsir.com</a> prior to arrival at RSYC

Date:

2.02 A yacht may be inspected at any time. If she does not comply with these Special Regulations her entry may be rejected, or she will liable to disqualification or such other penalty as may be prescribed by the national authority or the race organizers.

Issued v5 28/10/22 by:RMSIR

Name:

Tel: +603 31686964 Fax:+603 3168 8650 Email: info1@rmsir.com URL: <u>www.rmsir.com</u>

			S/PIC	Ins
Lay out o	n Chart Table or other Surface			
4.11.2	Navigational Charts, Light list and chart plotting equipment. If electronic only an independent alternative shall be onboard.			
		<u> </u>		
Lay out o	n Bunk(s)			
3.29.05	1 watertight handheld VHF radio transceiver, can be stowed in grab bag			
3.29.6	A VHF radio transceiver rated 24 Watts or greater, pref. with DSC function			
Additional Requirement	2 independent GPS Navigation Devices			
Advisory	An AIS Transponder is recommended			
4.8.1	First Aid Kit and First Aid Manual			
4.9.1	Foghorn			
4.16.1	Tools, spare parts, method to disconnect/sever standing rigging			
4.23.1	Electronic flares and 2 orange smoke flares			
Advisory	Two red parachute flares and four red hand flares			
5.1.1	Lifejacket with light, whistles etc, 1 for each crew, marked with boat name			
5.1.1 a)i)	Each lifejacket has crotch or thigh straps			
5.1.4	Each lifejacket inspected by person in charge, within last 12 months			
Advisory	Safety harness and lines for each crew member			
Below De	ck Inspection			
3.6.1	At least 2 exits in each hull which contains accommodation if LH greater than 8m, preferably 1 forward of the foremost mast or bulkhead free cabin to allow unimpeded egress			
3.8.2	Portlights that open inward labelled "NOT TO BE OPENED AT SEA"			

3.10.1	Sea cocks or valves on through-hull openings below waterline		
3.12.1	Heel of keel-stepped mast is secured to structure		
3.18.2	Toilet or fitted bucket, permanently installed		
3.22.1	Handholds below deck		
3.27.4	Spare bulbs for navigation lights (not required for LED)		
4.3.1	Tapered soft wood plug at each through-hull fitting		
4.5.1	A fire blanket adjacent to every cooking device with an open flame		
4.5.2	2 fire extinguishers, in different parts of the boat		
4.12.1	Safety equipment location chart		
At Helm, Ready for Rapid Deployment			
4.22.3	Lifebuoy with self-igniting light and drogue		
4.22.7	Heaving line min.6mm, 15-25m		
On Deck,	Where Stowed or Ready for Deployment		
	Hatch blocking devices attached and can be secured in place		
4.25.1	A strong, sharp knife, sheathed and securely restrained		
Rigged/Fitted to Demonstrate Use			
	Navigation lights, above sheerline and not obscured when sailing		
4.10.1	Radar reflector/ target enhancer		
4.26.2c	Either reefing to reduce the mainsail luff by 12% or a heavy weather jib		

Notes on storm sails/rig available			
General			
2.4.1	All equipment is readily available, adequately sized and functions		
2.4.2	Heavy items are permanently installed or securely fastened		
3.1.1	The boat is strongly built, seaworthy and watertight.		
3.8.1	Forward hatches open outward only		
3.8.3	Hatches are attached, above water at 90° heel & operable if capsized		
3.8.5 a)	Companionway sill is above local sheerline, or acceptable alternative		
3.9.1	Cockpit is strong, watertight and meets OSR size and drainage		
3.14.1	Double lifelines & pulpits surround entire deck, 600mm high		
3.23.1 a)	2 strong buckets, each with lanyard and 9 litre min capacity		
3.23.2	Permanently installed manual bilge pump operable with all hatches shut		
3.23.3	Bilge pump neither connects to cockpit drains nor discharges into cockpit		
3.24 a)	2nd compass, may be hand-held and/or electronic		
4.17.1	Boat's name on buoyant equipment		
4.18	Marine grade retro-reflective material on buoyant equipment		
6.4	Date of last Man Overboard Drill with current crew		
6.5	How many of this crew are first aid trained?		

Comments by Inspector:		
Signed		